



A mid-range vertical sliding unit with higher capacity spring balances that allow treatment of larger windows and also support thicker glass when increased levels of noise insulation are needed. With secure locking it is accredited to Secured by Design.



FEATURES

- Recessed finger lift on lower sash allows contra-sliding to assist with cleaning
- 28mm wide interlock stile with projecting finger pull
- Twin brush seals ensure high sealing efficiency
- Fixings concealed within the frame – trims not required
- Frames may be linked with a colour matched aluminium transom/mullion section

DIMENSIONS

Recommended maximum frame

Format	Height (mm)	Width (mm)
2 PANES	3000	1600

Maximum sash (h)1500mm x (w)1600mm, minimum sash (h)400mm x (w)400mm

Overall dimensions are subject to a maximum sash weight of 31kg, or 50kg by special request, and a minimum of 4.5kg

Sash height to width ratio should not normally exceed 1:3

A minimum frame to frame gap of 75mm is recommended for access to the outer window



FRAME COLOUR

Stock finish is white HIPCA 9910 semi-gloss

Any standard powder paint, wood grain finish or anodised finish to order

OPTIONS

Glazing	4mm to 8.8mm
Frames	Curved on plan
Ironmongery	H3 Recessed finger pull to upper sash
(see page 44/45)	H17 Cranked 'D' handle to upper sash
	L2 Lockable fitch catch
	L3 SBD Secure lockable fitch catch (2 per unit)
	L24 Sliding latch