

APEX WINDOWS LTD
UNIT 11 TELAMERE IND EST
ALBERT ROAD
LUTON

LU1 3QF
TEL: 01582 400807
FAX:

SUPPLIER ORDER (4 FRAMES)

KHURANA

OUR REF : 1383

WORKS ORDER D

JOB SPEC : Unglazed

DEL DATE : 30/12/1899 00:00:00

DATE : 8-Oct-25


Page 1 of 3

1 1 x White LINIAR Sculpt Casement

Design: Style 27

Location: BEDROOM

O/A Dim 1200mm x 1200mm



Frame (Head)	LSW012 57mm Sculpt En+ F	Frame (Cill)	LSW012 57mm Sculpt En+ F
Frame (Left jamb)	LSW012 57mm Sculpt En+ F	Frame (Right jamb)	LSW012 57mm Sculpt En+ F
Mullion	LSW021/022 67mm T/Z Se	Sash (Head)	LSW033 75mm Sculpt En+ T
Sash (Cill)	LSW033 75mm Sculpt En+ T	Sash (Left jamb)	LSW033 75mm Sculpt En+ T
Sash (Right jamb)	LSW033 75mm Sculpt En+ T	Frame drip bar	LAN108 Vented Head Drip
Cill	LSL150 150mm cill	Add-on (Head)	LAN106 20mm add-on
Ventilator (AddOn)	2 x 5000mm² Slot Vent	Colour	White
Sash colour	White	Cill colour	White
Drainage	Concealed/ base	Open in/out	Open out
Bead type	LSW041 28mm Sculptured b	Handle	1 White Casement Handle
Casement locking	Shootbolt	Friction stay	Egress easyclean
Viewed from	Viewed from outside	Glazed in/out	Glazed in
Glazing method	Glass (site)	Glazing thickness	28mm
Glass display group	Float	Frame top joint	Mitre
Frame bottom joint	Mitre	Sash top joint	Mitre
Sash #2 top joint	Mitre	Sash bottom joint	Mitre
Sash #2 bottom joint	Mitre	Addon joint	Square (Hor run thru)
Tran/Mull joints	Welded joint	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Mock sash horn	No mock sash horn	Hinge protectors	
Special handle		Glazing method	Glass (site)
Glass display group	Float	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Glass decoration	Georgian Bar	Glass decor width	18mm Bar
Glass decor colour	White	Glass decor other	Std Joints
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Glazing method	Glass (site)	Glass display group	Float
Glazing type	4-20-4 Clr Optiwhite/ Pilkingt	Glass decoration	Georgian Bar
Glass decor width	18mm Bar	Glass decor colour	White
Glass decor other	Std Joints	Spacer bar	20mm Black Thermobar
Gas Filling	Argon Gas Filled		

REMARKS:

A1 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm Clr Optiwhite
: Georgian Bar (444 x 971)
F1 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm Clr Optiwhite
: Georgian Bar (444 x 971)

APEX WINDOWS LTD
UNIT 11 TELaMERE IND EST
ALBERT ROAD
LUTON

LU1 3QF
TEL: 01582 400807
FAX:

SUPPLIER ORDER (4 FRAMES)

KHURANA


OUR REF : 1383
WORKS ORDER D
JOB SPEC : Unglazed
DEL DATE : 30/12/1899 00:00:00
DATE : 8-Oct-25

Page 2 of 3

2 1 x White LINIAR Sculpt Casement

Design: Style 27 Location: LOUNGE

O/A Dim 1200mm x 1200mm



Frame (Head)	LSW012 57mm Sculpt En+ F	Frame (Cill)	LSW012 57mm Sculpt En+ F
Frame (Left jamb)	LSW012 57mm Sculpt En+ F	Frame (Right jamb)	LSW012 57mm Sculpt En+ F
Mullion	LSW021/022 67mm T/Z Se	Sash (Head)	LSW033 75mm Sculpt En+ T
Sash (Cill)	LSW033 75mm Sculpt En+ T	Sash (Left jamb)	LSW033 75mm Sculpt En+ T
Sash (Right jamb)	LSW033 75mm Sculpt En+ T	Frame drip bar	LAN108 Vented Head Drip
Cill	LSL150 150mm cill	Add-on (Head)	LAN106 20mm add-on
Ventilator (AddOn)	2 x 5000mm² Slot Vent	Colour	White
Sash colour	White	Cill colour	White
Drainage	Concealed/ base	Open in/out	Open out
Bead type	LSW041 28mm Sculptured b	Handle	1 White Casement Handle
Casement locking	Shootbolt	Friction stay	Egress easyclean
Viewed from	Viewed from outside	Glazed in/out	Glazed in
Glazing method	Glass (site)	Glazing thickness	28mm
Glass display group	Float	Frame top joint	Mitre
Frame bottom joint	Mitre	Sash top joint	Mitre
Sash #2 top joint	Mitre	Sash bottom joint	Mitre
Sash #2 bottom Joint	Mitre	Addon joint	Square (Hor run thru)
Tran/Mull joints	Welded joint	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Mock sash horn	No mock sash horn	Hinge protectors	.
Special handle	.	Glazing method	Glass (site)
Glass display group	Float	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Glass decoration	Georgian Bar	Glass decor width	18mm Bar
Glass decor colour	White	Glass decor other	Std Joints
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Glazing method	Glass (site)	Glass display group	Float
Glazing type	4-20-4 Clr Optiwhite/ Pilkingt	Glass decoration	Georgian Bar
Glass decor width	18mm Bar	Glass decor colour	White
Glass decor other	Std Joints	Spacer bar	20mm Black Thermobar
Gas Filling	Argon Gas Filled		


REMARKS:

- A1** 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm Clr Optiwhite
: Georgian Bar (444 x 971)
F1 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm Clr Optiwhite
: Georgian Bar (444 x 971)

3 1 x White LINIAR Sculpt Casement

Design: Style FF Location: LOUNGE

O/A Dim 560mm x 560 / 0mm



Frame (Head)	LSW012 57mm Sculpt En+ F	Frame (Cill)	LSW012 57mm Sculpt En+ F
Frame (Left jamb)	LSW012 57mm Sculpt En+ F	Frame (Right jamb)	LSW012 57mm Sculpt En+ F
Sash (Head)	LSW033 75mm Sculpt En+ T	Sash (Cill)	LSW033 75mm Sculpt En+ T
Sash (Left jamb)	LSW033 75mm Sculpt En+ T	Sash (Right jamb)	LSW033 75mm Sculpt En+ T
Cill	No cill	Colour	White
Sash colour	White	Drainage	Concealed/ base
Open in/out	Open out	Bead type	LSW041 28mm Sculptured b
Handle	11 White Cranked Handle	Casement locking	Shootbolt
Friction stay	Standard friction stay	Viewed from	Viewed from outside
Glazed in/out	Glazed in	Glazing method	Glass (site)
Glazing thickness	28mm	Glass display group	Float
Frame top joint	Mitre	Frame bottom joint	Mitre
Sash top joint	Mitre	Sash #2 top joint	Mitre
Sash bottom joint	Mitre	Sash #2 bottom Joint	Mitre
Addon joint	Square (Hor run thru)	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Mock sash horn	No mock sash horn	Hinge protectors	.
Special handle	.		

REMARKS:

- A1** *Cut-templ* 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm
Clr Optiwhite : (381 x 381)

APEX WINDOWS LTD
UNIT 11 TELaMERE IND EST
ALBERT ROAD
LUTON

LU1 3QF
TEL: 01582 400807
FAX:

SUPPLIER ORDER (4 FRAMES)

KHURANA

OUR REF : 1383

WORKS ORDER D

JOB SPEC : Unglazed

DEL DATE : 30/12/1899 00:00:00

DATE : 8-Oct-25


Page 3 of 3

4 1 x White LINIAR Sculpt Casement

Design: Style 5

Location:

O/A Dim 600mm x 1000mm



Frame (Head)	LSW012 57mm Sculpt En+ F	Frame (Cill)	LSW012 57mm Sculpt En+ F
Frame (Left jamb)	LSW012 57mm Sculpt En+ F	Frame (Right jamb)	LSW012 57mm Sculpt En+ F
Sash (Head)	LSW033 75mm Sculpt En+ T	Sash (Cill)	LSW033 75mm Sculpt En+ T
Sash (Left jamb)	LSW033 75mm Sculpt En+ T	Sash (Right jamb)	LSW033 75mm Sculpt En+ T
Frame drip bar	LAN108 Vented Head Drip	Cill	LSL150 150mm cill
Add-on (Head)	LAN106 20mm add-on	Ventilator (AddOn)	5000mm² Slot Vent
Colour	White	Sash colour	White
Cill colour	White	Drainage	Concealed/ base
Open in/out	Open out	Bead type	LSW041 28mm Sculptured b
Handle	11 White Cranked Handle	Casement locking	Shootbolt
Friction stay	Egress easyclean	Viewed from	Viewed from outside
Glazed in/out	Glazed in	Glazing method	Glass (site)
Glazing thickness	28mm	Glass display group	Float
Frame top joint	Mitre	Frame bottom joint	Mitre
Sash top joint	Mitre	Sash #2 top joint	Mitre
Sash bottom joint	Mitre	Sash #2 bottom Joint	Mitre
Addon joint	Square (Hor run thru)	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled
Mock sash horn	No mock sash horn	Hinge protectors	.
Special handle	.	Glazing method	Glass (site)
Glass display group	Float	Glazing type	4-20-4 Clr Optiwhite/ Pilkingt
Glass decoration	Georgian Bar	Glass decor width	18mm Bar
Glass decor colour	White	Glass decor other	Std Joints
Spacer bar	20mm Black Thermobar	Gas Filling	Argon Gas Filled

REMARKS:

A1 4-20-4 Clr Optiwhite/ Pilkington KS : 4mm Clr Pilkington KS : 4mm Clr Optiwhite
: Georgian Bar (421 x 771)

EXTRAS

QUANTITY

mm